

SiteSelect™ Posts

Stationary Posts

Stationary posts are equipped with a leveling bolt to account for uneven floors.

- Height includes leveling bolt (completely tightened) and post cap. Leveling bolt can be adjusted 1/2" (13mm).
- Foot plates may be ordered separately and installed in place of leveling foot.
- Replacement leveling bolts
Zinc Cat. No. RPF04-004 Stainless Steel Cat. No. RPF04-004C
- Replacement post cap for standard posts
Black Cat. No. RPC06-035



SiteSelect Posts feature double grooves every 8" (203mm) to aid assembly.

Model No. Chrome	Model No. Metroseal 3 with Microban	Model No. Stainless Steel	Height		Approx. Pkd. Wt.	
			(in.)	(mm)	(lbs.)	(kg)
7P			7 ³ / ₈	187	1/2	0.3
13P	13PK3	13PS	14 ³ / ₈	365	1	0.5
27P		27PS	28 ³ / ₈	720	1 ³ / ₄	0.75
33P	33PK3	33PS	34 ³ / ₈	873	2	0.9
54P	54PK3	54PS	54 ⁷ / ₁₆	1382	3	1.4
63P	63PK3	63PS	62 ⁷ / ₁₆	1585	3 ¹ / ₂	1.6
74P	74PK3	74PS	74 ¹ / ₂	1892	4	1.8
86P	86PK3	86PS	86 ¹ / ₂	2197	5	2.3
*96P			96 ¹ / ₂	2450	5 ¹ / ₂	2.5

*96P should not be used on units less than 24" (610mm) deep. Consult Metro Engineering for alternate recommendations.

Mobile Posts (For use with Stem Casters)

- Height includes post cap.

Model No. Chrome	Model No. Metroseal 3 with Microban	Model No. Stainless Steel	Height		Approx. Pkd. Wt.	
			(in.)	(mm)	(lbs.)	(kg)
27UP		27UPS	27 ³ / ₄	704	1 ³ / ₄	0.75
33UP	33UPK3	33UPS	33 ³ / ₄	857	2	0.9
54UP	54UPK3	54UPS	53 ¹³ / ₁₆	1366	3	1.4
63UP	63UPK3	63UPS	61 ¹³ / ₁₆	1570	3 ¹ / ₂	1.6
	70UPK3		69 ³ / ₄	1771	3 ³ / ₄	1.7
74UP	74UPK3	74UPS	73 ⁷ / ₈	1876	4	1.8
86UP	86UPK3	86UPS	85 ⁷ / ₈	2181	4 ¹ / ₂	2.0

Staked Posts (For use with Truck Dollies)

- Each post connects to the truck dolly through the stem receptacle. The stem receptacle is staked into the bottom of the post to ensure a durable connection in abusive mobile applications.
- Each includes a leveling/connecting bolt.

Model No. Chrome	Model No. Stainless Steel	Height		Approx. Pkd. Wt.	
		(in.)	(mm)	(lbs.)	(kg)
54P-STKD	54PS-STKD	54 ⁷ / ₁₆	1382	3	1.4
63P-STKD	63PS-STKD	62 ⁷ / ₁₆	1585	3 ¹ / ₂	1.6
74P-STKD	74PS-STKD	74 ¹ / ₂	1892	4	1.8

Swedged Posts (For use with Stem Casters in Cart Wash Applications)

- Each post has an aluminum cap swedged into the top of the post.

Model No. Stainless Steel	Height		Approx. Pkd. Wt.	
	(in.)	(mm)	(lbs.)	(kg)
33UPS-SW	33 ³ / ₄	857	2	0.9
54UPS-SW	53 ¹³ / ₁₆	1366	3	1.4
63UPS-SW	61 ¹³ / ₁₆	1570	3 ¹ / ₂	1.6

Special Length Posts

Special length cut posts are available. Consult your Metro representative for more information.