

**PRODUCT INFORMATION****Style:** LN 10

<b>Sizing:</b>	<u>Size</u>	<u>Part #</u>	<u>Overedge</u>
	XXSmall	135639	Red
	XSmall	135640	Green
	Small	135641	Yellow
	Medium	135642	Blue
	Large	135643	White
	XLarge	135644	Orange

**Registered Brand Name:** Whizard  
**Classification:** Cut Resistant**PRODUCT DESCRIPTION**

**Description:** High Performance Antimicrobial Cut Glove  
**Color:** Black & White (gray) shell / Blue cuff  
**Material:** Combination of High Performance, Durable Fibers and Stainless Steel; Antimicrobial CFR 21 - Approved for Food Contact

**Sold by:** Piece  
**Packaging (Inner Pack):** 6 Pieces  
**Packaging (Case Pack):** 120 Pieces

**CUT PROTECTION PERFORMANCE INFORMATION**

**Test Method:** ASTM F1790-97  
**Test Results:** 3538 grams / 7.80lbs.  
ANSI Level 5

**ABRASION PROTECTION PERFORMANCE INFORMATION**

**Test Method:** ASTM D3884-05  
**Test Results:** 8750 revs (cycles)

**WASHING INSTRUCTIONS**

Always wash similar products of the same materials together. This will eliminate different material types from being effected by non-recommended chemicals. Rinse all gloves thoroughly in cold water to ensure the release of particles in the products. If pre-soaking use luke warm water to ensure good particle softening. Mild detergents or chemicals should be used to enhance the laundering process. All products should be laundered using a mild soap and detergent. Use a warm water wash with a temperature not to exceed 160°F (71°C). Wash time should not be longer than 15 to 20 minutes. Use a rinse cycle for the product in cold water. Repeat above as often as needed to ensure a thoroughly clean product. It is important to use a high extraction speed to thoroughly remove all excess moisture. Tumble dry glove in a temperature not higher than 150°F (67°C) for a time of 15 to 20 minutes; adjustments in dry time may increase depending on quantity and weight of the products. Temperatures should not exceed 150°F (67°C).

**CAUTION**

Gloves are cut resistant but are not cut or puncture-proof. Do not subject to high-speed, serrated blades or intentional slashings.