

Heavy Duty Chain & Cable Lubricant

PRODUCT DESCRIPTION:

JAX Heavy Duty Chain & Cable Lubricant is a heavy-duty, multi-purpose lubricant formulated to be the best available for rigorous industrial applications. A combination of superior corrosion-resistant, antiwear, rust-preventive grease with effective penetrant provides the base. To this, the extreme lubricity and antifriction characteristics of Graphite and Molybdenum Disulfide ("Moly") are added. This custom formulation enables the lubricants to reach deep inside to the inner strands of cables and wire rope as well as the pins and rollers of industrial chains, where lubrication is critical. With proper application, JAX Heavy Duty Chain & Cable Lubricant drastically reduces internal friction and extends the life of chains and cables by 200% or more.

PRODUCT BENEFITS:

Due to its water-repelling nature and rust-preventing features, JAX Heavy Duty Chain & Cable Lubricant performs equally well outdoors when exposed to the elements. For best results, allow 10-15 minutes of set-up time.

APPLICATION:

Uses for JAX Heavy Duty Chain & Cable Lubricant include:

- Construction equipment
- Industrial chains
- Farm machinery
- Conveyor chains
- Wire ropes and slings
- Roller and lift chains on material handling equipment
- Gates
- Overhead cranes
- Elevators
- Tower cranes

TECHNICAL DATA:

Propellant:	Propane and n-Butane
Flash Point:	430°F (221°C) Grease, typical
Pour Point:	10°F (-12°C) Grease, typical
Spray Pattern:	Shotgun Blast
Viscosity:	Grease: 300-350 SUS @ 100°F, typical
Texture:	Dark Grease with Fine MoS ₂ and Graphite Particulate
Appearance:	Black Grease
Consistency:	Light
Specific Gravity:	0.886 for Concentrate, typical

AEROSOL PACKAGING:

11 oz. net weight aerosol cans (12/case) — Part # JAX104

BULK PACKAGING:

Trigger Spray Bottles (16 Fl. Oz., 12/case), Gallons (4/case), 35-Lb. pails and 400-lb. drums — Part # 00200



Heavy-Duty Chain & Cable Lubricant



NSF International / Nonfood Compounds Registration Program

October 11, 2004

Ms. Patty Riek
PRESSURE-LUBE, INC. JAX
W134 N5373 CAMPBELL DRIVE
MENOMONEE FALLS, WI 53051
UNITED STATES

RE: JAX CHAIN & CABLE LUBRICANT (Aerosol)
Category Code: H2
NSF Registration No. 133894

Dear Ms. Patty Riek:

NSF has processed the application for Registration of **JAX CHAIN & CABLE LUBRICANT (Aerosol)** to the NSF Registration Guidelines for Proprietary Substances and Nonfood Compounds (2004), which are available at <http://www.nsf.org>. The NSF Nonfood Compounds Registration Program is a continuation of the USDA product approval and listing program, which is based on meeting regulatory requirements including FDA 21 CFR for appropriate use, ingredient and labeling.

This product is acceptable as a lubricant where there is no possibility of food contact (H2) in and around food processing areas. Such compounds may be used as lubricants, release agents, or antirust films on equipment and machine parts in locations in which there is no possibility of the lubricant or lubricated part contacting edible products.

NSF Registration of this product is current when the NSF Registration Number, Category Code, and Registration Mark appear on the NSF-approved product label, and the registered product name is included in the current NSF White Book Listing of Nonfood Compounds at the NSF website (<http://www.nsf.org>). The NSF Registration Mark can be downloaded from the NSF website, at http://www.nsf.org/business/about_NSF/nsf_marks_download.asp.

NSF Listing of all registered Nonfood compounds by NSF International is not an endorsement of those compounds, or of any performance or efficacy claims made by the manufacturer.

Registration status may be verified at any time via the NSF web site, at <http://www.nsf.org>. Changes in formulation or label, without the prior written consent of NSF, will void registration, and will supersede the on-line listing.

Sincerely,

Carmen Grindatti
NSF Nonfood Compounds Registration Program

Company No: N05625

Distributed By:

PRESSURE-LUBE
America's Finest Lubricants

W134 N5373 Campbell Drive • Menomonee Falls, WI 53051
262.781.8850 • 800.782.8850 • FAX 262.781.3906
www.jax.com