AC OR BATTERY POWERED

Parts List

- ☐ (1) Four-person floor mount wash station Model 58FA, NSF/ANSI 372 Low Lead Model 58FAL, Model 58FB or NSF/ANSI 372 Low Lead Model 58FBL
- ☐ (1) Leg assembly set
- ☐ (6) Washers and nuts for connection sink to leg assembly set
- (4) AC or battery powered sensor faucet assembly
- (4) Connecting tubes for valve to spout connection Model 1007 or 1007L
- ☐ (8) Fittings, brass, 0.375" male compression and 0.375" male NPT Model 1008 or 1008L
- (2) Strainer assembly with basket Model 1010
- ☐ (4) Mixing check valve Model 201L

Tools Required

- □ Tape Measure
- ☐ Adjustable Wrench
- ☐ Drill Motor and Drill Bits
- ☐ Pipe Wrench
- □ Level
- □ Safety Glasses
- ☐ Screw Drivers: 1 Phillips & 1 Standard
- □ Pencil
- ☐ Socket Wrench

Installation Instructions

Step 1

- 1. Place wash station sink on the leg assembly. Secure legs to bowl with hardware provided.
- 2. Place Wash Station Sink at the desired location.
- 3. Mark the floor where the mounting holes are at the base of the legs. See illustration A.
- 4. Drill holes as required for mounting hardware. Hardware Not Included.

Step 2

- 1. Install faucets to the sink following the instructions provided with sensor unit.
- 2. Install strainer assembly.
- 3. Install mixing check valve to inlet filter on each faucet.

Step 3

- 1. Position the wash station sink to pre-drilled holes and secure sink to the floor.
- 2. Connect waste line or drain pipe to the strainer assembly. Not included.
- 3. Install elbow fittings onto the valves.
- 4. Install valves under the platform of the leg assembly.
- $\ensuremath{\mathsf{5}}.$ Attach connecting tubes from the spout to the valves.
- 6. Connect water supply lines (Hot and Cold) from the water source to valves. Not included.

Step 4

- 1. Remove aerator from the spouts and flush the water system.
- 2. Replace aerator to the spout.
- 3. Check for leaks and tighten connections if necessary.

Step 5

- 1. Seal gap between bowl and leg assembly as shown in illustration B.
- When mounting against wall, it is recommended sealing the top of the backsplash to wall as shown on illustration C.



Illustration A



Illustration B



Illustration C