

☐ **G1814BC** Eye Wash, Wall Mounted, Stainless Steel Bowl and Cover



Application: Eye wash for wall mounting. Unit has stainless steel cover to protect bowl from dust, dirt and other contaminants. Two GS-Plus™ spray-type spray heads deliver a flood of water for rinsing eyes.

Spray Head Assembly: Two GS-Plus™ spray heads. Each head has an internal flow control and filter to remove impurities from the water flow.

Valve: 1/2" IPS chrome plated brass stay-open ball valve. Valve is US-made with chrome plated brass ball and Teflon® seals.

Bowl: 11 1/2" stainless steel with bowl cover. Cover is raised automatically when flag handle is activated. Cover closes when handle is returned to closed position.

Mounting: Heavy duty cast aluminum wall bracket with powder coated finish.

Supply: 1/2" NPT female inlet.

Waste: 1 1/4" NPT female outlet.

Sign: ANSI-compliant identification sign.

Quality Assurance: Unit is completely assembled and water tested prior to shipment.

Available Options

- ☐ **HS** Auxiliary hand-held drench hose for rinsing eyes, face or body.
- ☐ **T** Chrome plated brass tailpiece and trap with 1 1/2" IPS waste connection.
- ☐ **TP** 1 1/2" OD chrome plated brass tailpiece.
- ☐ **TMV** G3600 thermostatic mixing valve precisely blends hot and cold water to deliver warm (tepid) water as provided by ANSI Z358.1-2004. Refer to "Tempering Units" section for complete technical and product selection information.



ETL Listed 101496.
Units have been tested
to and comply with
ANSI Z358.1 - 2004