

Oil-Only 20-Gallon Kit Refill #RSPKO-20 - Absorbs up to 16.4 Gallons



Refill your SpillTech® Oil-Only 20-Gallon Spill Kit to ensure fast response.

 Contents-only Refill. Conveniently packaged to easily restock your Spill Kit. Includes a variety of sorbents to handle spills of oil and other petroleum-based fluids — while repelling water. Don't see what you're looking for? We can customize a Spill Kit or Refill to your exact specifications, including the container, its contents and accessories, with no upcharge! Contact your local Distributor for details.

RSPKO-20 Specifications

Dimensions: 20" W x 23" L x 10" H **Shipping** 20" W x 23" L x 10" H

Dimensions:

Sold as: 1 per package

Composition: N/A

Absorbency: Up to 17.1 gal. per package

per Pallet: 32 Incinerable: Yes Ship Class: 150

Includes: 25 - 15" x 19" White Oil-Only

HeavyWeight SonicBonded Pads

(WPB100H)

4 - 3" x 4' White Oil-Only Sorbent

Socks (WSO430)

2 - 18" x 18" White Oil-Only Sorbent

Pillows (WPIL1818)

2 - 30" x 6" x 60" Yellow Disposal

Bags & Ties (A-DISPBAG)

1 - Pair Nitrile Gloves (A-GLV-NIT)

1 - Safety Goggles (A-GOG)

1 - 3" x 5" Vinyl Spill Kit Label (A-

KITLABEL)

Metric Equivalent Specifications

Dimensions: 50.8cm W x 58.4cm L x 25.4cm H **Shipping** 50.8cm W x 58.4cm L x 25.4cm H

Dimensions:

Absorbency: Up to 64.7 L per package



Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other) Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other) Email: spilltech@spilltech.com

RSPKO-20 Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

33 CFR 154.1047(c)(2) - Concerning navigation and navigable waters, a facility which handles, stores or transports Group V petroleum oils must identify response plan resources such as containment booms and other methods.

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

Technical Documents:

(Available at spilltech.com)

Product Data Sheet (PDS)



Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other) Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other) Email: spilltech@spilltech.com