

**PRODUCT SPECIFICATION SHEET****PRODUCT INFORMATION****Style:** Metalguard® Sleeve

<b>Sizing:</b>	<b>Size</b>	<b>Part #</b>				
		<u>Standard</u>	<u>Thumb Hole</u>	<u>Wide Top</u>	<u>Wide Top Thumb Hole</u>	
	10"	SK-10-KSC	NA	NA	NA	
	14"	SK-14-KSC	NA	NA	NA	
	16"	SK-16-KSC	NA	NA	NA	
	18"	SK-18-KSC	SK-18H-KSC	SK-18W-KSC	NA	
	22"	SK-22-KSC	SK-22H-KSC	SK-22W-KSC	NA	
	24"	SK-24-KSC	NA	SK-24W-KSC	SK-24WH-KSC	

**Registered Brand Name:** Metalguard®  
**Classification:** Cut Resistant**PRODUCT DESCRIPTION**

**Description:** High Performance Cut Resistant Sleeve  
**Color:** Yellow / Green  
**Material:** Combination of High Performance Fiber with Stainless Steel

**Sold by:** Piece  
**Packaging (Inner Pack):** 12 Pieces  
**Packaging (Case Pack):** 48 Pieces

**CUT PROTECTION PERFORMANCE INFORMATION**

**Test Method:** ASTM F1790-97  
**Test Results:** 2,059 grams / 4.54lbs.  
ANSI Level 4

**ABRASION PROTECTION PERFORMANCE INFORMATION**

**Test Method:** ASTM D3884-05  
**Test Results:** 963 revs (cycles)

**WASHING INSTRUCTIONS**

Always wash similar products of the same materials together. This will eliminate different material types from being effected by non-recommended chemicals. Rinse all gloves thoroughly in cold water to ensure the release of particles in the products. If pre-soaking use luke warm water to ensure good particle softening. Mild detergents or chemicals should be used to enhance the laundering process. All products should be laundered using a mild soap and detergent. Use a warm water wash with a temperature not to exceed 160°F (71°C). Wash time should not be longer than 15 to 20 minutes. Use a rinse cycle for the product in cold water. Repeat above as often as needed to ensure a thoroughly clean product. It is important to use a high extraction speed to thoroughly remove all excess moisture. Tumble dry glove in a temperature not higher than 150°F (67°C) for a time of 15 to 20 minutes; adjustments in dry time may increase depending on quantity and weight of the products. Temperatures should not exceed 150°F (67°C).

**CAUTION**

Gloves are cut resistant but are not cut or puncture-proof. Do not subject to high-speed, serrated blades or intentional slashings.