Ask the Expert ... Ask Miller.

Miller Rope, Wire Rope and Web Lanyards REDUCES FALL ARREST FORCES with SofStop® Shock Absorber

SofStop Shock Absorber pack is designed with a specially-woven inner core that smoothly expands to reduce fall arrest forces.





SKU	Material	Number of Legs	Harness Connection	Anchorage Connection	Special Features	Standard Length						
■ MILLER LANYARDS WITH SOFSTOP SHOCK ABSORBER												
ANSI A10.32												
928LS/18INYL	_	N/A	Locking snap hook	D-ring	_	18-in. (457 mm)						
901RLS-2/6FTWH*	Rope	One	Locking snap hook	Locking snap hook	=	6-ft. (1.8 m)						
903RLS-2/6FTWH*	Rope	One	Locking snap hook	Locking snap hook	Adjustable	4-ft. (1.2 m) to 6-ft. (1.8 m)						
907LS/6FTYL	Wire rope	One	Locking snap hook	Locking snap hook	=	6-ft. (1.8 m)						
907NLS/6FTYL	Vinyl-coated wire rope	One	Locking snap hook	Locking snap hook	_	6-ft. (1.8 m)						
910WLS/6FTYL	Webbing	One	Locking snap hook	Locking snap hook	Adjustable	4-ft. (1.2 m) to 6-ft. (1.8 m)						
913WLS/6FTYL	Webbing	One	Locking snap hook	Locking snap hook	_	6-ft. (1.8 m						
940WLS/6FTGN	Webbing	One	Locking snap hook	Locking snap hook	SofStop Double Pack**	6-ft. (1.8 m)						
980WLS/6FTGN	Webbing	Two	Locking snap hook	Locking snap hook	SofStop Double Pack**	6-ft. (1.8 m)						
8798/6FTYL	Webbing	Two	Locking snap hook	Locking snap hooks	=	6-ft. (1.8 m)						
8798R/6FTYL	Webbing	Two	Locking snap hook	Locking rebar hooks	_	6-ft. (1.8 m)						

^{*}To order polyester rope, add "-5" to the corresponding SKU number (Ex.: 903RLS-5/6FTWH)

Miller Vinul-Coated Shock-Absorbing Lanuards

Miller Vinyl-Coated Shock-Absorbing Lanyards feature a special vinyl coating on the webbing to protect against a variety of liquids that could compromise overall performance. Miller Vinyl-Coated Products are effective in a wide range of applications. including: Food Processing, Petrochemical, Water Treatment, Painting, Billboards and General Industry.



FEATURES

- SofStop Shock Absorber pack is designed with a specially-woven inner core that smoothly expands to reduce fall arrest forces
- Includes heavy-duty back-up safety strap
- Zinc-plated steel snap hooks
- User-rated to 310 lbs. (140.6 kg)



SKU	Material	Number of Legs	Harness Connection	Anchorage Connection	Standard Length
MILLER VINYL ANSI Z359	-COATED SHOCK-ABSOR	BING LANYAR	DS		
913PC/6FTGN	Vinyl-coated webbing	One	Locking snap hook	Locking snap hook	6-ft. (1.8 m)
922PCR/6FTGN Vinyl-coated webbing		One	Locking snap hook	Locking rebar hook	6-ft. (1.8 m)
8798PC/6FTGN	Vinyl-coated webbing	Two	Locking snap hook	Locking snap hooks	6-ft. (1.8 m)
8798PCR/6FTGN Vinyl-coated webbing		Two	Locking snap hook	Locking rebar hooks	6-ft. (1.8 m)

^{*}SofStop Double Pack for 12-ft. (3.7 m) free fall. Duty-rated 400 lbs. (181.4 kg) capacity. Locking Snap Hook – 3/4-in. (19 mm) gate opening; Locking Rebar Hook – 2-1/2-in. (64 mm) gate opening.