



TWIN-LEG SELF RETRACTING LIFELINE

Provides a significant increase in mobility and safety, allowing user to “leap-frog” while moving from one location to another. Each lifeline works independently, extending up to 6 feet and automatically retracting, providing fall protection and mobility 100% of the time.

- Twin-leg 100% tie-off SRL provides continuous protection
- Built-in anchorage connector for direct attachment to harness or anchorage
- Compact, lightweight design does not hinder movement
- Replaces a simple lanyard with the convenience of a retractable lifeline



Model Shown
3102000 Attached to
1102000 Harness

HOOK STYLE	HOOK THROAT SIZE (IN)	RATED GATE CAPACITY (LBS.)	SWIVEL HOOK	TIE-BACK	SRL WEIGHT CAPACITY (LBS.)	6 ft. (1.8 m)		7.5 ft. (2.3 m)	
						Model	Part No.	Model	Part No.
ALUMINUM REBAR HOOK	2 1/4	3,600	■	■	310	3102005			
					350			3102102	
					310	3102000			
					420	3102016			
STEEL REBAR HOOK	2 1/4	3,600	■	■	350				3102101
					310	3102003			
					420	3102017			
	3	3,600			310	3102008			
	STEEL SNAP HOOK	3/4	3,600	■	■	310			
420									3102115
310						3102002			
420						3102014			
310						3102001			
					420	3102015			
APPROXIMATE WEB SRL WEIGHT						5 lbs. (2.2 kg)		5.5 lbs. (2.2 kg)	
APPROXIMATE TIE-BACK WEB SRL WEIGHT						—		6.5 lbs. (3 kg)	
APPROXIMATE DEPTH						2.6" (6.6 cm)		2.6" (6.6 cm)	
APPROXIMATE WIDTH						7.2" (18.2 cm)		7.2" (18.2 cm)	
APPROXIMATE HEIGHT						3.8" (9.7 cm)		3.8" (9.7 cm)	

* Other models available; please contact DBI-SALA®.

3102100

TALON™ TIE-BACK MODEL SHOWN

All twin-leg Talon™ SRLs include: Delta Comfort Pad and 2 ea. Lanyard Keepers



SINGLE AND TWIN-LEG TALON™ HOOK OPTIONS



Standard Hook
3/4" (19 mm)
Gate Opening -
3,600 lb. (16Kn)
Gate Strength



Swiveling Hook
3/4" (19 mm)
Gate Opening -
3,600 lb. (16Kn)
Gate Strength



WrapBax™ Hook
3/4" (19 mm)
Gate Opening -
5,000 lb. Gate
Strength



2000112—Saflok™ Steel Carabiner
11/16" (17.5 mm)
Gate Opening -
3,600 lb. (16Kn)
Gate Strength



2000114—Saflok™ Steel Carabiner
2-3/16" (55.5 mm)
Gate Opening -
3,600 lb. (16Kn)
Gate Strength



Aluminum Rebar Hook
2-1/4" (57 mm) Gate
Opening - 3,600
lb. (16Kn) Gate
Strength



Flat Steel Rebar Hook
2-1/2" (62.5 mm) Gate
Opening - 3,600
lb. (16Kn) Gate
Strength



Saflok Max™ Steel Rebar Hook
3" (76.2 mm) Gate
Opening - 3,600
lb. (16Kn) Gate
Strength