

CONNECTING DEVICES

Extended
service life



RL20P-Z7/20FT

RL65G-Z7/65FT



8174/U



300L/50FTBL

Miller MightyLite™ Self-Retracting Lifelines

- Corrosion-resistant stainless steel and aluminum components extend service life
- Double-swivel design prevents lifeline from twisting and kinking
- Narrow payout port prevents intrusion of dirt and debris
- No annual factory recertification required, keeping units on the jobsite for increased productivity
- Carabiner for attaching to anchorage and tagline included
- Meets applicable OSHA, ANSI Z359, ANSI A10.32 and CSA standards

SKU	Description	Length
▶ RL20P-Z7/20FT	1-in. Polyester webbing; ANSI Z359 locking snap hook	20 ft.
RL50P-Z7/50FT	1-in. Polyester webbing; ANSI Z359 locking snap hook	50 ft.
▶ RL20G-Z7/20FT	3/16-in. Galvanized wire rope; ANSI Z359 locking snap hook	20 ft.
▶ RLS30G-Z7/30FT	3/16-in. Galvanized wire rope; ANSI Z359 locking snap hook	30 ft.
▶ RL50G-Z7/50FT	3/16-in. Galvanized wire rope; ANSI Z359 locking snap hook	50 ft.
RL65G-Z7/65FT	3/16-in. Galvanized cable; ANSI Z359 locking snap hook	65 ft.
RL100G-Z7/100FT	3/16-in. Galvanized cable; ANSI Z359 locking snap hook	100 ft.
RL130G-Z7/130FT	3/16-in. Galvanized wire rope; ANSI Z359 locking snap hook	130 ft.
RL175G-Z7/175FT	3/16-in. Galvanized wire rope; ANSI Z359 locking snap hook	175 ft.

Note: Stainless steel models available

▶ Rapid Response Program – Same Day Shipping! Consult Customer Care for up-to-date availability.



Rope Grabs and Lifelines


SKU	Description
▶ 8174/U	Manual Rope Grab – Stainless steel, manual rope grab for use with 5/8-in. or 3/4-in. synthetic rope
▶ 300L/50FTBL	Polypropylene blend rope lifeline with locking snap hook and loop; 5/8-in diameter; 50 ft.

▶ Rapid Response Program – Same Day Shipping! Consult Customer Care for up-to-date availability.

ANCHORAGE CONNECTORS



8183/6FTGN



470/

Miller Cross-Arm Strap Anchorage Connector

- Designed to wrap around approved I-beams or other structures for a secure attachment point for lanyards and self-retracting lifelines
- 400 lbs. maximum capacity

SKU	Description
▶ 8183/6FTGN	6 ft. web Cross-Arm Strap wraps around I-beams and other structures and attaches with a 2-in. D-ring that slips through a 3-in. D-ring

▶ Rapid Response Program – Same Day Shipping! Consult Customer Care for up-to-date availability.



Miller Wire Hook Anchor

- Stainless steel wire hook is fast and easy to use
- 400 lbs. maximum capacity

SKU	Description
470/	Connects to various approved anchorages including railings, small I-beams, angle iron and scaffolding. Squeeze the spring-loaded hook and slip the large opening over the approved structure

Call Customer Care at 800 430-5490.

Call Honeywell Technical Service at 800-873-5242 or visit www.millerfallprotection.com.