

20" and 18" INDUSTRIAL GRADE FANS

Ideal for gyms, auditoriums, schools, churches and industrial spaces that need powerful air circulation.

PRODUCT INFORMATION

Motor

3-speed, 1/6 HP, 120V, 1 phase, totally enclosed, ball bearing, permanently lubricated, permanent split capacitor

Controls

Rear mounted rotary switch (models 9420, 9418)

Rear mounted pull cord switch (models 9020, 9518, 9320 9718, 9520, 9618)

Power Cord

Black, 9', 3-conductor, SJT type

Coating

Blade, Guard, and Mounts are powder coated steel

Compliance

ETL, OSHA

Height

Adjustable from 54" to 64" (model 9420)

Adjustable from 52" to 62" (model 9418)



Pedestal
9420




Pedestal
9418



Secondary support cable included on Wall, Ceiling, and I-Beam Mount models.



Wall Mount
9020



Wall Mount
9518



Ceiling Mount
9320



Ceiling Mount
9718



I-Beam Mount
9520



I-Beam Mount
9618

SPECIFICATIONS

MODEL	DESCRIPTION	BLADE SIZE	PRODUCT DIMENSIONS	WEIGHT (LBS.)	CUBE (FEET)	LIST PRICE
9420	20" Pedestal Fan	20"	26.5"L x 23.25"W x 64"H	34.3	3.76	\$247.50
9020	20" Wall Mount Fan		26.5"L x 16.5"W x 29.5"H	26.0	3.47	\$196.00
9320	20" Ceiling Mount Fan		26.5"L x 10.5"W x 29.5"H	23.7	3.47	\$247.50
9520	20" I-Beam Mount Fan		36"L x 22"W x 42"H	47.6	3.47	\$335.00
9418	18" Pedestal Fan	18"	24"L x 24"W x 62"H	31.4	3.25	\$247.50
9518	18" Wall Mount Fan		24"L x 16.5"W x 28"H	24.8	2.80	\$196.00
9718	18" Ceiling Mount Fan		24"L x 10.5"W x 28"H	23.1	2.80	\$247.50
9618	18" I-Beam Mount Fan		24"L x 37.5"W x 38.5"H	36.9	4.90	\$335.00

PERFORMANCE

TYPE	CFM			RPM			AMPS			WATTS			DB A		
	HIGH	MED	LOW	HIGH	MED	LOW	HIGH	MED	LOW	HIGH	MED	LOW	HIGH	MED	LOW
20" 1/6 HP ⁴	3670	3330	2940	1500	1310	1050	1.60	1.30	1.10	184	155	130	62	55	48
18" 1/6 HP ⁵	3190	2970	2660	1500	1300	1100	1.52	1.30	1.00	180	150	125	67	58	49

⁴ Includes models 9420, 9020, 9320, 9520 • ⁵ Includes models 9418, 9518, 9718, 9618
Tested in accordance with AMCA standard 230-99. • Specifications are subject to change.

