

PRODUCT INFORMATION**Style:** Defender 10

Sizing:	<u>Size</u>	<u>Part #</u>	<u>Overedge</u>	
		<u>Std. Cuff</u>	<u>Ext. Cuff</u>	
	XXSmall	N/A	135445	Red
	XSmall	135478	135432	Green
	Small	135479	135433	Yellow
	Medium	135480	135434	Blue
	Large	135481	135435	White
	XLarge	135482	135436	Orange
	XXLarge	135582	N/A	Black

**Registered Brand Name:** Whizard®
Classification: Cut Resistant**PRODUCT DESCRIPTION**

Description: High Performance Antimicrobial Cut Resistant Glove
Color: White Shell / Blue Cuff
Material: Patented Combination of High Performance Fibers, Stainless Steel and Antimicrobial Fibers
Cuff: CFR21 - Approved for Food Contact
Regular or Extended Cuff

Sold by: Piece
Packaging (Inner Pack): 6 pieces
Packaging (Case Pack): 72 pieces

CUT PROTECTION PERFORMANCE INFORMATION

Test Method: ASTM F1790-97
Test Results: 3,883 grams / 8.56 lbs.
ANSI Level 5

ABRASION PROTECTION PERFORMANCE INFORMATION

Test Method: ASTM D3884-05
Test Results: 6,406 revs (cycles)

WASHING INSTRUCTIONS

Always wash similar products of the same materials together. This will eliminate different material types from being effected by non-recommended chemicals. Rinse all gloves thoroughly in cold water to ensure the release of particles in the products. If pre-soaking use luke warm water to ensure good particle softening. Mild detergents or chemicals should be used to enhance the laundering process. All products should be laundered using a mild soap and detergent. Use a warm water wash with a temperature not to exceed 160°F (71°C). Wash time should not be longer than 15 to 20 minutes. Use a rinse cycle for the product in cold water. Repeat above as often as needed to ensure a thoroughly clean product. It is important to use a high extraction speed to thoroughly remove all excess moisture. Tumble dry glove in a temperature not higher than 150°F (67°C) for a time of 15 to 20 minutes; adjustments in dry time may increase depending on quantity and weight of the products. Temperatures should not exceed 150°F (67°C).

CAUTION

Gloves are cut resistant but are not cut or puncture-proof. Do not subject to high-speed, serrated blades or intentional slashings.

Wells Lamont Industrial 6640 W Touhy Ave Niles IL 60714
Toll-Free 1.800.247.3295 Fax 1.847.470.1026 www.wellslamontindustrial.com

JC 9/12