

aero[®] resilient floor care

The AERO[®] Line of floor finishes provides a finish for every application and maintenance technique employed by today's floor maintenance supervisor. The line ranges from hard polymer finishes for low maintenance situations to soft polymer finishes where frequent maintenance is required.

HIGHLIGHTS

- Modified acrylic polymers
- Unsurpassed leveling
- Outstanding gloss
- Reduced sensitivity to ambient application conditions
- Excellent burnish response with no powdering or dusting
- High durability
- Decreased labor cost through less frequent need to buff, burnish and recoat, and a reduction in the number of floor strippings

TYPICAL PROPERTIES

- Specific Gravity: **1.04**
- Solids: **22%**
- pH: **8.5**
- James Static Coefficient of Friction: **0.6**
- Leveling: **Excellent**
- Film Formation: **Excellent**
- Gloss: **Excellent**
- Water resistance: **Excellent**
- Detergent resistance: **Excellent**
- Removability: **Excellent**
- Black heal mark resistance: **Excellent**
- Odor: **Mild acrylic**
- Appearance: **White emulsion**

SAFETY CAUTIONS

- Keep out of reach of children.
- It is recommended that protective gloves and safety glasses be worn when using this product. Make sure there is adequate ventilation.
- Refer to M.S.D.S. for additional safety information.

HMS RATINGS

Flammability



Peak Floor Finish

Unsurpassed Leveling, Excellent Initial Gloss, Gloss Retention, and Durability

A 22% solids floor finish formulation based on the latest generation of modified acrylic polymers that provides unsurpassed leveling, excellent initial gloss, gloss retention, and durability. It may be used in low maintenance mop/recoat programs as well as with high speed burnishing equipment.

APPLICATION (new or existing floors)

1. Thoroughly strip floor with an Aero floor finish remover.
2. Rinse floor thoroughly with clean water.
3. Apply a sealer base (optional) to worn floors or high traffic floors to improve wear-resistance and enhance gloss.
4. Apply finish in uniform thin coats allowing time to dry thoroughly between coats. Allow for longer drying time in damp weather.

MAINTENANCE

Dust mop, sweep or damp mop as necessary. If desired, burnish with electrical, battery or propane high-speed buffers using a synthetic or synthetic/natural blend pad. Depending on traffic, burnish 1-3 times a week.



Atlanta, Georgia / Dallas, Texas

Manufactured exclusively by:

ABC Compounding Co., Inc. • Atlanta, GA 30321



CLASSIFIED BY
UNDERWRITERS LABORATORIES INC.®
AS TO SLIP RESISTANCE ONLY.
2M05

6561TDS_1309