

Titan™ Positioning and Restraint Lanyards

Rope and Web Lanyards recommended for “work positioning” and “restraint” only.



SKU	Material	Harness Connection	Anchorage Connection	Standard Length*
■ TITAN POSITIONING AND RESTRAINT LANYARDS				
ANSI A10.32				
T9111R/6FTWH	Rope 5/8-in. (16 mm)	Locking snap hook	Locking snap hook	6-ft. (1.8 m)
T9111W/6FTAF	Webbing	Locking snap hook	Locking snap hook	6-ft. (1.8 m)
T9112R/6FTWH	Rope 5/8-in. (16 mm)	Locking snap hook	Large locking rebar hook	6-ft. (1.8 m)
T9112W/6FTAF	Webbing	Locking snap hook	Large locking rebar hook	6-ft. (1.8 m)
T9113W/6FTAF	Webbing	Locking snap hook	Small locking rebar hook	6-ft. (1.8 m)

*Also available in lengths from 2-ft (6 m) to 10-ft. (3 m). Locking snap hook – 3/4-in. (19 mm) gate opening. Small locking rebar hook – 1-3/4-in. (44 mm) gate opening. Large locking rebar hook – 2-1/2-in. (64 mm) gate opening.

Titan™ Positioning Assemblies



Always
Know Your
Fall Clearance
Pg. 20

SKU	Description
■ TITAN POSITIONING ASSEMBLIES	
ANSI Z359	
T8221W-Z7/27INYL*	Web positioning assembly w/two locking snap hooks & one large locking rebar hook
ANSI A10.32	
T8221/	Rebar chain assembly w/two locking snap hooks & one large locking rebar hook
T8221W/27INYL*	Web positioning assembly w/two locking snap hooks & one large locking rebar hook

*Also available in 35-in. (889 mm) or 40-in. (1016 mm). Locking snap hook – 3/4-in. (19 mm) gate opening. Large locking rebar hook – 2-1/2-in. (64 mm) gate opening.

Titan™ Cross-Arm Anchorage Connectors



6-ft. (1.8 m) web **Cross-Arm Strap** features a D-ring which slips through a web loop; available in lengths from 3 ft. (.9 m) to 10 ft. (3 m).

T7314/3FTAF

T7314/6FTAF

Titan™ Equipment/Accessory Bag



Light-duty **Equipment/Accessory Bag** w/Titan logo, zipper closure and wrap-around carrying straps 13-in. x 8-in. x 8-in. (330 mm x 203 mm x 203 mm).

T702B/BK