



HEADSUP LITE™ 2690 LED
■ **RUN TIME:** 10 hrs. 30 mins.
■ **LIGHT OUTPUT:** 60 LUMENS

HEAD LIGHTS

FREE YOUR HANDS

For two-handed tasks on the factory floor or at base camp, Pelican™ head lights lead the way. Super bright Incandescent and LED models include a rubber strap for helmet/hard hat use as well as an adjustable cloth strap. The lightweight 2690 features a rotary bezel switch that is easy to operate, even while wearing bulky gloves.

HEADSUP LITE™ 2600					
LIGHT SOURCE			Krypton (primary) Krypton (back-up)		
			4 AA Alkaline (Included)		
			3.81" (9.7cm)		
			CI II III D2		
ANSI STANDARDS					
	LIGHT OUTPUT	RUNTIME	BEAM DISTANCE	PEAK BEAM INTENSITY	WATERPROOF & SUBMERSIBLE

HEADSUP LITE™ 2610 LED					
LIGHT SOURCE			LED		
			3 AAA Alkaline (Included)		
			1.49" (3.8cm)		
			CI D1		
ANSI STANDARDS					
	LIGHT OUTPUT	RUNTIME	BEAM DISTANCE	PEAK BEAM INTENSITY	WATER RESISTANT

HEADSUP LITE™ 2620					
LIGHT SOURCE			Xenon (high) LED (low)		
			3 AAA Alkaline (Included)		
			2.16" (5.5cm)		
			CI D1		
ANSI STANDARDS					
	LIGHT OUTPUT	RUNTIME	BEAM DISTANCE	PEAK BEAM INTENSITY	WATER RESISTANT

HEADSUP LITE™ 2640					
			Halogen (high) LED (low)		
			4 AA Alkaline (Included)		
			2.63" (6.7cm)		
			CI D2		
LIGHT OUTPUT	RUNTIME	BEAM DISTANCE	PEAK BEAM INTENSITY	WATER RESISTANT	






























HEADSUP LITE™ 2680 RECOIL™ LED					
			Recoil™ LED		
			4 AA Alkaline (Included)		
			4.64" (11.8cm)		
			CI II III D2		
LIGHT OUTPUT	RUNTIME	BEAM DISTANCE	PEAK BEAM INTENSITY	WATERPROOF & SUBMERSIBLE	

HEADSUP LITE™ 2690 LED					
			LED		
			3 AAA Alkaline (Included)		
			2.81" (7.1cm)		
			CI II III D1		
LIGHT OUTPUT	RUNTIME	BEAM DISTANCE	PEAK BEAM INTENSITY	WATER RESISTANT	

















2710 LED HEADLIGHT				NEW						
LIGHT SOURCE					LED					
BATTERIES					2 AAA Alkaline (Included)					
LENGTH					N/A					
COLORS										
APPROVALS					N/A					
ANSI STANDARDS										
	LIGHT OUTPUT		RUNTIME		BEAM DISTANCE		PEAK BEAM INTENSITY		WATER RESISTANT	

2720 LED HEADLIGHT					NEW	
LIGHT SOURCE						LED
						3 AAA Alkaline (Included)
						N/A
						
						N/A
BATTERIES						
LENGTH						
COLORS						
APPROVALS						
ANSI STANDARDS	<div><div><div>HIGH</div><div>80</div><div>LUMENS</div></div><div><div>LOW</div><div>5</div><div>LUMENS</div></div><div><div>HIGH</div><div>8h</div></div><div><div>LOW</div><div>175h</div></div><div><div>HIGH</div><div>56m</div></div><div><div>LOW</div><div>15m</div></div><div><div>HIGH</div><div>790cd</div></div><div><div>LOW</div><div>60cd</div></div><div><div>FL 1 STANDARD</div><div></div></div></div>					

LIGHT SOURCE					
BATTERIES					
LENGTH					
COLORS					
APPROVALS					
ANSI STANDARDS					

	TACTICAL/DUTY LED LIGHTS													
	Cat No.	Model Name	Light Source	Batteries	ANSI Light Output	ANSI Runtime	ANSI Beam Distance	ANSI Peak Beam Intensity	ANSI Waterproof/ Submersible/ Water Resistant	Approvals	Length	Weight with Batteries	Colors	
LED LIGHTS	2330	M6 2330 LED	LED	2 CR123 Lithium (Included)	100 LUMENS	6h	93m	2184cd	IPX4	N/A	5.51" (14 cm)	5.5 oz. (0.16 kg)		
	2360	2360 LED	LED	2 AA Alkaline (Included)	110 (High) 10 (Low) LUMENS	2h (High) 40h (Low)	158m (High) 49m (Low)	6242cd (High) 615cd (Low)	IPX4	N/A	6.2" (15.7 cm)	5.4 oz. (0.15 kg)		
	2390	M6 3W 2390 LED	LED	2 CR123 Lithium (Included)	177 LUMENS	2h 30m	155m	6002cd	IPX4	N/A	5.31" (13.5 cm)	5.6 oz. (0.16 kg)	 	
	3330	PM6 3330 LED	LED	2 CR123 Lithium (Included)	90 LUMENS	4h 45m	88m	1959cd	IPX4	N/A	5.27" (13.4 cm)	3.45 oz. (0.1 kg)	  	
	7060	7060 LED	LED	1 3.7 V, 2200 mAh Lithium-Ion (Included)	160 LUMENS	2h	254m	16,101cd	IPX4	N/A	8.65" (22 cm)	10.4 oz. (0.29 kg)		
	8060	8060 LED	LED	4 C SIZE Ni-MH (Included)	179 LUMENS	6h 45m	279m	19,525cd	IPX4	N/A	12.67" (32.2 cm)	23.2 oz. (0.66 kg)		
	1830	L4™ 1830 LED	LED	3 AAAA Alkaline (Included)	5 LUMENS	32h	13m	44cd	IPX4	CI D1	6.2" (15.7 cm)	1.2 oz. (0.03 kg)	 	
	1930	L1™ 1930 LED	LED	4 LR 44 Alkaline (Included)	12 LUMENS	4h 15m	17m	70cd	IPX4	CI D1	2.64" (6.7 cm)	0.9 oz. (0.03 kg)	 	
	2130	Mini Flasher™ 2130 LED	LED	2 L1154 Alkaline (Included)	4.7 LUMENS (Non ANSI)	130h (Non ANSI)	N/A	N/A	IPX7	N/A	1.73" (4.4 cm)	0.5 oz. (0.01 kg)		
	2130IR	Mini Flasher™ 2130IR LED	LED	2 L1154 Alkaline (Included)	N/A	65h (Non ANSI)	N/A	N/A	IPX7	N/A	1.73" (4.4 cm)	0.5 oz. (0.01 kg)		
	2220	VB3™ 2220 LED	LED	2 CR2032 Lithium (Included)	9 LUMENS	34h	12m	38cd	IPX4	CI D1	3.5" (8.9 cm)	1 oz. (0.03 kg)	     *	
	2220NV	VB3™ 2220NV LED	LED	2 CR2032 Lithium (Included)	1 LUMEN (Non ANSI)	100h (Non ANSI)	N/A	N/A	IPX4	C1D1	3.5" (8.9 cm)	1 oz. (0.03 kg)		
	2365	2365 LED Flex Neck	LED	2 AA Alkaline (Not Included)	49 LUMENS	7h	81m	1644cd	IPX4	N/A	21.92" (55.7 cm)	9.3 oz. (0.26 kg)		
	2010	SabreLite™ 2010 LED	LED	3 C Alkaline (Not included)	109 LUMENS	32h	144m	5189cd	IPX7	CI II III D1	8.11" (20.6 cm)	13.4 oz. (0.38 kg)	 	
	2010PL	SabreLite™ 2010 LED Photoluminescent	LED	3 C Alkaline (Not included)	109 LUMENS	32h	144m	5189cd	IPX7	CI II III D1	8.11" (20.6 cm)	13.4 oz. (0.38 kg)		
	2020	SabreLite™ 2020 Recoil™ LED	Recoil™ LED	3 C Alkaline (Not included)	75 LUMENS	6h 30m	113m	3211cd	IPX4	CI II D1	8.75" (22.2 cm)	14.7 oz. (0.42 kg)	 	
	2410	StealthLite™ 2410 LED	LED	4 AA Alkaline (Included)	126 LUMENS	7h 30m	161m	6500cd	IPX7	CI II III D1	7" (17.8 cm)	7.3 oz. (0.21 kg)	 	

* translucent color

	Cat No.	Model Name	Light Source	Batteries	ANSI Light Output	ANSI Runtime	ANSI Beam Distance	ANSI Peak Beam Intensity	ANSI Waterproof/ Submersible/ Water Resistant	Approvals	Length	Weight with Batteries	Colors
LED LIGHTS	2410PL	StealthLite™ 2410 LED Photoluminescent	LED	4 AA Alkaline (Included)	126 LUMENS	7h 30m	161m	6500cd	IPX7	CI II III D1	7" (17.8 cm)	7.3 oz. (0.21 kg)	
	2460	StealthLite™ Rechargeable 2460 LED	LED	4 AA NiMH (Included)	112 LUMENS	4h 30m	153m	5828cd	IPX7	CI II D2	7" (17.8 cm)	7.8 oz. (0.22 kg)	 
	2490	2490 LED (with Traffic Wand)	LED	4 AA Alkaline (Not included)	51 LUMENS	15h	88m	1930cd	IPX7	N/A	12.5" (31.7 cm)	8.2 oz. (0.23 kg)	
	3610	Little Ed™ 3610 LED	LED	4 AA Alkaline (Included)	126 LUMENS	7h 30m	161m	6500cd	IPX7	CI II III D1	7.51" (19.1 cm)	10.5 oz. (0.3 kg)	 
	3610PL	Little Ed™ 3610 LED Photoluminescent	LED	4 AA Alkaline (Included)	126 LUMENS	7h 30m	161m	6500cd	IPX7	CI II III D1	7.51" (19.1 cm)	10.5 oz. (0.3 kg)	
	3660	Little Ed™ Rechargeable 3660 LED	LED	4 AA NiMH (Included)	112 LUMENS	4h 30m	153m	5828cd	IPX7	CI II D2	7.51" (19.1 cm)	10.56 oz. (0.3 kg)	 
	2600	HeadsUp Lite™ 2600	Krypton	4 AA Alkaline (Included)	18 LUMENS	3h 30m	27m	203cd	IPX7	CI II III D2	3.81" (9.7 cm)	9.7 oz. (0.27 kg)	
	2610	HeadsUp Lite™ 2610 LED	LED	3 AAA Alkaline (Included)	30 LUMENS	19h	28m	194cd	IPX4	CI D1	1.49" (3.8 cm)	3.2 oz. (0.09 kg)	
	2620	HeadsUp Lite™ 2620	Xenon (High) LED Low)	3 AAA Alkaline (Included)	26 (High) 14 (Low) LUMENS	2h 15m (High) 18h (Low)	44m (High) 29m (Low)	491cd (High) 216cd (Low)	IPX4	CI D1	2.16" (5.5 cm)	4.8 oz. (0.14 kg)	
	2640	HeadsUp Lite™ 2640	Halogen (High) LED Low)	4 AA Alkaline (Included)	29 (High) 16 (Low) LUMENS	2h 45m (High) 17h (Low)	46m (High) 20m (Low)	586cd (High) 103cd (Low)	IPX4	CI D2	2.63" (6.7 cm)	10.9 oz. (0.31 kg)	
HEAD LIGHTS	2680	HeadsUp Lite™ 2680 Recoil™ LED	Recoil™ LED	4 AA Alkaline (Included)	69 LUMENS	9h 30m	123m	3788cd	IPX7	CI II III D2	4.64" (11.8 cm)	9.7 oz. (0.27 kg)	
	2690	HeadsUp Lite™ 2690 LED	LED	3 AAA Alkaline (Included)	60 LUMENS	10h 30m	81m	1664cd	IPX4	CI II III D1	2.81" (7.1 cm)	4.1 oz. (0.12 kg)	
	2710	2710 LED Headlight	LED	2 AAA Alkaline (Included)	24 (High) 7 (Low) LUMENS	2h (High) 5h (Low)	34m (High) 14m (Low)	285cd (High) 50cd (Low)	IPX4	N/A	N/A	2.8 oz. (0.08 kg)	
	2720	2720 LED Headlight	LED	3 AAA Alkaline (Included)	80 (High) 5 (Low) LUMENS	8h (High) 175h (Low)	56m (High) 15m (Low)	790cd (High) 60cd (Low)	IPX4	N/A	N/A	3.8 oz. (0.11 kg)	