Universal Features

These self-closing foot or knee-operated valves completely eliminate the possibility of contamination from germ laden or dirty faucets. Columbia valves are made of rough chrome-plated cast brass and stainless steel.

Models ending in S are reinforced with all stainless steel components to withstand extreme usage.



Series 100 Valves

Design that sets an industry standard.

- · Easy lift-up Pedals for cleaning
- · All valves are tested at 150 PSI after assembly.
- · Stainless steel pedals, bolts and nuts
- · 1/2" NPT inlets, 3/8" NPT outlets
- · NSF/ANSI 372 Low Lead Content (Models ending in L)









Model 102L

All Models

Foot Operated Valves







Model 106S Model 106L

Knee Operated Valves









Mixing Check Valve Model 201L

Valve Repair Kit Model 1061L

- · Fits all the above 100 series valves
- · Sold one each and works for both hot & cold side
- NSF/ANSI 372 Low Lead Content (Models ending in L)

Connecting Hoses and Fittings Model 1006L

- · 30" hose with 2 each 1008 fittings
- · Used with wall mount sinks
- · 0.375" compression female
- · NSF/ANSI 372 Low Lead Content (Models ending in L)

Model 1007L

- · 41" hose with 2 each 1008 fittings
- · Used with floor mount sinks and wash stations
- 0.375" compression female
- · NSF/ANSI 372 Low Lead Content (Models ending in L)

Model 1008L

- · Brass elbow fitting
- Male 0.375" compression and male 0.375" NPT
- · NSF/ANSI 372 Low Lead Content (Models ending in L)









Model 1006L

Model 1007L



Model 1008L