WELLS LAMONT

Industrial

PRODUCT SPECIFICATION SHEET

PRODUCT INFORMATION

Style: DB Glove

Size Part # **Overedge** Sizing: XSmall 135533 Green Small 135534 Yellow Medium 135535 Blue Large 135536 White 135537 Orange XLarge

Registered Brand Name: Whizard®
Classification: Cut Resistant



PRODUCT DESCRIPTION

Description: DB Glove **Color:** Gray

Material: Constructed From High Performance Fibers and Wire

Fingers: Added Food Approved Puncture Resistant Material on Thumb and Index Fingers

Approval: CFR21 - Approved for Food Contact

Sold by: Piece
Packaging (Inner Pack): 6 Pieces
Packaging (Case Pack): 72 Pieces

CUT PROTECTION PERFORMANCE INFORMATION

Test Method:ASTM F1790-97 - CPPTTest Results:8.50 lbs / 3,855 grams

ANSI Level 5

PUNCTURE PERFORMANCE INFORMATION

Test Method: ASTM Standard F1342 - Accutest 1000 unit

Test Results: 11.50 lbs (patch material)

WASHING INSTRUCTIONS

Always wash similar products of the same materials together. This will eliminate different material types from being effected by non-recommended chemicals. Rinse all gloves thoroughly in cold water to ensure the release of particles in the products. If pre-soaking use luke warm water to ensure good particle softening. Mild detergents or chemicals should be used to enhance the laundering process. All products should be laundered using a mild soap and detergent. Use a warm water wash with a temperature not to exceed 160°F (71°C). Wash time should not be longer than 15 to 20 minutes. Use a rinse cycle for the product in cold water. Repeat above as often as needed to ensure a thoroughly clean product. It is important to use a high extraction speed to thoroughly remove all excess moisture. Tumble dry glove in a temperature not higher than 150°F (67°C) for a time of 15 to 20 minutes; adjustments in dry time may increase depending on quantity and weight of the products. Temperatures should not exceed 150°F (67°C).

CAUTION

Gloves are cut resistant but are not cut or puncture-proof. Do not subject to high-speed, serrated blades or intentional slashings.

Wells Lamont Industrial 6640 W Touhy Ave Niles IL 60714
Toll-Free 1.800.247.3295 Fax 1.847.470.1026 www.wellslamontindustrial.com

JC 7/13