



**QC 120 S**

## Coverall

**QC 122 B YL xx 0012 00**

Bound seams, MD-6X

**QC 122 B YL xx 0012 BN**

Bound seams, MD-6X

**QC 122 T YL xx 0004 00**

Taped seams, SM-6X

Attached hood

Front zipper closure

Storm flap with tape closure

Elastic wrists

Attached socks<sup>1</sup>



## Coverall

**QC 127 S YL xx 0012 00**

Serged seams

Attached hood

Front zipper closure

Elastic wrists

Elastic ankles

SM-7X



## Coverall

**QC 127 B YL xx 0012 00**

Bound seams, SM-7X

**QC 127 T YL xx 0004 00**

Taped seams, SM-7X

**QC 127 B GY xx 0012 00**

Bound seams, MD-4X

**QC 127 T GY xx 0004 00**

Taped seams, SM-7X

Attached hood

Front zipper closure

Storm flap

Elastic wrists

Elastic ankles



## Frock

**QC 210 S YL xx 0012 00**

Serged seams

Collar

Front snap closure

SM-5X



## Apron

**QC 273 B YL xx 0024 00**

**QC 273 B YL xx 0100 00**

Bound neck & ties

Bib style

36" long

One size fits all



## Apron

**QC 275 B YL xx 0025 00**

Bound seams

Raw edge neck with snaps

Attached long sleeves

Waist ties

Elastic wrists

44" long

SM-4X



## Apron

**QC 278 B YL xx 0012 00**

Bound seams

Attached long sleeves

Bound yoke neck without snaps

Waist ties

Elastic wrists

52" long

One size fits all



## Shirt

**QC 303 S YL xx 0012 00**

Serged seams

Collar

Front snap closure

Long sleeve

MD-4X



## Pants

**QC 350 S YL xx 0012 00**

Serged seams

Elastic waist

MD-4X



Only BN option codes are Berry compliant.

Please note that Tychem® fabrics have different permeation performance. Please check SafeSPEC® 2.0 on our website for permeation data that meets your specific needs.

Stock/Made to Order designations are based on sales volume and production efficiencies. Therefore, designations are subject to change without notice.

<sup>1</sup>These Tychem® garments have attached socks made of the garment material. These attached socks must be worn inside protective outer footwear and are not suitable as outer footwear. These attached socks do not have adequate durability or slip resistance to be worn as the outer foot covering.

**Storm flaps:** All standard bound and taped seam coveralls have a single storm flap with a pressure-sensitive tape closure. Serged seam coveralls do not have a storm flap.

Seams and closures have less barrier than fabric.

Serged and/or bound seams are degraded by some hazardous liquid chemicals, such as strong acids, and should not be worn when these chemicals are present.

Note: Not all sizes available in all styles.

**WARNING:** Tychem® should not be used around heat, flames, sparks or in potentially flammable or explosive environments. Only Tychem® ThermoPro, Tychem® Reflector® and Tychem® TK styles 600T/601T (with aluminized outer suit) garments are designed and tested to help reduce injury during escape from a flash fire. Users of Tychem® ThermoPro, Tychem® Reflector® and Tychem® TK styles 600T/601T (with aluminized outer suit) garments should not knowingly enter an explosive environment. Consult the Tychem® user manual, located on our website, for instructions on proper use, care and maintenance of your Tychem® garments.

## Sleeve

**QC 500 B YL xx 0200 00**

Bound seam

Elastic top

Elastic wrist

18" length

One size fits all



