

For Model #		Description	Part #	Nozzle Material
	74H	Air Miser Nozzle	74HNB	Brass
-	LZR600 LZ650 74S 74SK	Rubber Tip Nozzle	74NRT	Rubber Tip Brass Threads
•	75LJ U75LJ	Venturi Nozzle	75LJNA 75LJNS 75LJNN	Zinc Steel Nylon
	75XT U75XT	Xtra Thrust Nozzle	75XTNA 75XTNS 75XTNN	Aluminum Steel Nylon
-	80LJ 80LJ	Whisper Jet Nozzle	80LJNA	Aluminum
=	80WJ	Whisper Jet Nozzle	80WJNA	Aluminum
O = •	900	Venturi Nozzle	900NA	Aluminum
1000	9005	Venturi Nozzle with Air Shield	900SNA	Aluminum

Note: All replacement nozzles must be paired with the proper Guardair Safety Air Gun to comply with OSHA standards.

HIGH PERFORMANCE CONNECTORS & COUPLERS

HIGH FLOW SERIES: Engineered to allow twice the flow of comparable sized standard connectors and couplers. Recommended for all Guardair products and for pneumatic tools such as small drills, screwdrivers and air hammers using 1/4" and 3/8" I.D. air hose. Couplers accept standard U.S. Industrial Interchange type connectors. Work Range: 40°F to 250°F (-40°C to 107°C); 0 - 150 psi.

CONNECTORS			COUPLERS		
Part #	Male Thread			Part #	Male Thread
14H03M 38H03M	1/4" NPT 3/8" NPT		>	14H01M	1/4" NPT
	Female Thread				Female Thread
14H03F 38H03F	1/4" FNPT 3/8" FNPT	←	→	14H01F 38H01F	1/4" FNPT 3/8" FNPT
	Hose Barb				Hose Barb
14H04M 38H04M	1/4" ID Hose 3/8" ID Hose		→	14H02M	1/4" ID Hose