

☐ **G1814P** Eye Wash, Wall Mounted, Plastic Bowl



**Application:** Eye wash for wall mounting. Two GS-Plus™ spray-type spray heads deliver a flood of water for rinsing eyes.

**Spray Head Assembly:** Two GS-Plus™ spray heads. Each head has a “flip top” dust cover, internal flow control and filter to remove impurities from the water flow.

**Valve:** 1/2” IPS chrome plated brass stay-open ball valve. Valve is US-made with chrome plated brass ball and Teflon® seals.

**Bowl:** 11 1/2” diameter orange ABS plastic.

**Mounting:** Heavy duty cast aluminum wall bracket with corrosion resistant powder coated finish.

**Supply:** 1/2” NPT female inlet.

**Waste:** 1 1/4” NPT female outlet.

**Sign:** ANSI-compliant identification sign.

**Quality Assurance:** Unit is completely assembled and water tested prior to shipment.

## Available Options

- ☐ **DC** Stainless steel dust cover for each spray head.
- ☐ **GRN** Green ABS plastic bowl.
- ☐ **YEL** Yellow ABS plastic bowl.
- ☐ **HS** Auxiliary hand-held drench hose for rinsing eyes, face or body.
- ☐ **SC** Self-closing ball valve.  
*Note: Eye washes with self-closing valves do not comply with ANSI Z358.1 - 2004.*
- ☐ **T** Chrome plated brass tailpiece and trap with 1 1/2” IPS waste connection.
- ☐ **TP** 1 1/2” OD Chrome plated brass tailpiece.
- ☐ **TMV** G3600 thermostatic mixing valve precisely blends hot and cold water to deliver warm (tepid) water as provided by ANSI Z358.1-2004. Refer to “Tempering Units” section for complete technical and product selection information.