

Miller Rope Grabs

Miller Rope Grabs move easily up and down vertical lifelines to provide continuous fall protection. Trailing models offer complete hands-free operation for increased productivity. In the event of a fall, Miller rope grabs lock quickly.

■ FEATURES

- Compact design; corrosion-resistant stainless steel construction
- Lightweight and easy to use
- Rated to 310-lbs. (140.6 kg) capacity

8173/U



8174/U



8175/U



8175SLS-Z7/3FTYL



SKU

Description

■ MILLER ROPE GRABS

ANSI Z359

- 8175-Z7/** Trailing Rope Grab – Stainless steel trailing rope grab w/anti-panic feature for use with 5/8-in. (16 mm) rope
8175SLS-Z7/3FTYL Trailing Rope Grab – 8175-Z7/ with attached 3-ft. (1 m) SofStop shock-absorber for use with 5/8-in. (16 mm) rope

ANSI A10.32

- 8172/U** Miller MicroLoc™ Trailing Rope Grab – Compact, stainless steel trailing rope grab for use with 5/16-in. (8 mm) wire rope
8173/U Miller MicroLoc™ Trailing Rope Grab – Compact, stainless steel trailing rope grab for use with 5/8-in. (16 mm) rope
8174/U Manual Rope Grab – Stainless steel manual rope grab for use with 5/8-in. (16 mm) or 3/4-in. (19 mm) synthetic rope
8174MLS4/4FTYL Manual Rope Grab – 8174 w/attached 4-ft. (1.2 m) Manyard shock-absorbing lanyard w/locking snap hook
8174RLS/2FTWH Manual Rope Grab – 8174 w/attached 2-ft. (0.6 m) rope lanyard w/locking snap hook
8174WLS/2FTYL Manual Rope Grab – 8174 w/attached 2-ft. (0.6 m) web lanyard w/locking snap hook
98174LS/3FTYLU Manual Rope Grab – 8174 w/attached SofStop shock absorber w/locking snap hook
8175/U Trailing Rope Grab – Stainless steel trailing rope grab for use with 5/8-in. (16 mm) rope
8175RLS/2FTWH Trailing Rope Grab – 8175 w/attached 2-ft. (.6 m) rope lanyard w/locking snap hook
8175WLS/3FTYL Trailing Rope Grab – 8175 w/attached 3-ft. (1 m) web lanyard w/locking snap hook
8175SLS/3FTYL Trailing Rope Grab – 8175 w/SofStop shock absorber w/locking snap hook

CSA

- 8174/C** Manual Rope Grab – Stainless steel manual rope grab w/anti-panic feature for use with 5/8-in. (16 mm) or 3/4-in. (19 mm) synthetic rope
8175/C Trailing Rope Grab – Stainless steel trailing rope grab w/anti-panic feature for use with 5/8-in. (16 mm) rope

Locking Snap Hook – 3/4-in. (19 mm) gate opening.

Miller Lifelines

Synthetic rope lifeline with a minimum tensile strength of 5,000 lbs. (22 kN). **Standard lifeline lengths are 25 ft. (7.6 m), 50 ft. (15 m), 75 ft. (23 m), and 100 ft. (30 m); additional lengths are available.**



300L-Z7/100FTBL

SKU

Description

■ MILLER LIFELINES

ANSI Z359

- 300L-Z7/25FTBL** 5/8-in. (16 mm) diameter polypropylene blend rope w/locking snap hook & loop; 25-ft. (7.6 m)
300L-Z7/50FTBL 5/8-in. (16 mm) diameter polypropylene blend rope w/locking snap hook & loop; 50-ft. (15 m)
300L-Z7/100FTBL 5/8-in. (16 mm) diameter polypropylene blend rope w/locking snap hook & loop; 100-ft. (30 m)

ANSI A10.32

- 194R-2*** Nylon rope lifeline w/carabiner & thimble; 5/8-in. (16 mm) diameter
194R-5* Polyester rope lifeline for greater chemical resistance w/carabiner & thimble; 5/8-in. (16 mm) diameter
195R-2* Nylon rope lifeline w/thimbles; 5/8-in. (16 mm) diameter
195R-5* Polyester rope lifeline for greater chemical resistance w/thimbles; 5/8-in. (16 mm) diameter
300L/25FTBL 25-ft. (7.6 m); constructed of 5/8-in. (16 mm) polypropylene blend rope; locking snap hook & loop
300L/30FTBL 30-ft. (9 m); constructed of 5/8-in. (16 mm) polypropylene blend rope; locking snap hook & loop
300L/50FTBL 50-ft. (15 m); constructed of 5/8-in. (16 mm) polypropylene blend rope; locking snap hook & loop
300L/75FTBL 75-ft. (23 m); constructed of 5/8-in. (16 mm) polypropylene blend rope; locking snap hook & loop
300L/100FTBL 100-ft. (30 m); constructed of 5/8-in. (16 mm) polypropylene blend rope; locking snap hook & loop

*Must specify length when ordering.

Miller Safety Straps

NF Series

A 1-3/4-in. (44 mm) wide, 100% nylon safety strap offers a friction buckle to adjust the length of the strap quickly and easily.

YR Series

Strong safety strap, made of a six-ply nylon, remains flexible in all types of weather conditions. Tongue buckle adjuster included for quick, safe adjustment.

6NFLS/6FTYL



6YRLS/6FTBR



SKU

Description

Length

■ MILLER NF SERIES SAFETY STRAPS

ANSI A10.32

- 6NFLS/6FTYL** 1-3/4-in. (44 mm) wide, 100% nylon safety strap w/ friction buckle 6-ft. (1.8 m) length
7NFLS/7FTYL 1-3/4-in. (44 mm) wide, 100% nylon safety strap w/ friction buckle 7-ft. (2.1 m) length

■ MILLER YR SERIES SAFETY STRAPS

ANSI A10.32

- 6YRLS/6FTBR** Strong, six-ply nylon safety strap w/tongue buckle adjuster 6-ft. (1.8 m) length
7YRLS/7FTBR Strong, six-ply nylon safety strap w/tongue buckle adjuster 7-ft. (2.1 m) length

GRAVITY KILLS

DEFY IT!



Safety at Height Solutions

MILLER®

by Honeywell