

ANCHORAGE CONNECTORS**Miller Fusion™ Roof Anchor Posts**

- Permanent or temporary solution for roof safety
- Versatile single-point anchor adapts to a wide range of roof designs
- Protects worker by maintaining a secure connection to the structure; protects the structure with a unique energy-absorbing load distribution system

SKU	Description	Designed to Accommodate
X10000	Standing Seam Roofing	Standing seam spacing from 11.75-in. to 17-in.
▶ X10001	Standing Seam Roofing	Standing seam spacing from 11.75-in. to 21.25-in.
X10002	Standing Seam Roofing	Standing seam spacing from 11.75-in. to 24-in.
X10010	Metal Sheathing Roofing	Metal sheathing with minimum thickness of 24 gauge (0.024-in.)
X10011	Metal Sheathing Roofing	Metal sheathing with minimum thickness of 24 gauge (0.024-in.). Trapezoidal spacing of 8-in. to 20-in. in one-inch increments
X10030	Membrane/Built-up Roofing	Fastens through membrane, insulation and into metal sheathing, wood sheathing or concrete with a combined thickness of up to 5.5-in.
X10031	Membrane/Built-up Roofing	Fastens through membrane, insulation and into metal sheathing, wood sheathing or concrete with a combined thickness of > 5.5-in. up to 10.5-in.
X10020	Multi-Purpose Metal Sheathing, Wood and Concrete Roofing (no hardware included)	With Miller approved hardware, accommodates: metal sheathing with minimum thickness of 24 gauge (0.024 in.). Trapezoidal spacing of 8-in. to 20-in. in one-inch increments. Plywood with minimum thickness 5/8-in. CDX. Concrete decking with minimum thickness of 6.5-in. and minimum concrete compressive strength of 3000 PSI (20.7 MPa)

Note: Additional models available for wood sheathing, concrete roofing and multi-purpose applications



Standing Seam



Metal Sheathing



Membrane


Temporary Anchors

SKU	Description
▶ 17D-1/	Steel twist-lock carabiner; 1-in. gate opening. Meets ANSI Z359
▶ 18D-1/	Large, steel twist-lock carabiner; 2-in. gate opening. Meets ANSI Z359
18D-2/	Large, aluminum twist-lock carabiner; 2-1/4-in. gate opening
RA30-1	Reusable chain with 'O' ring; steep-pitched or flat roof
9065	Lightweight beam trolley adjusts to fit beam flanges from 3-in. to 4-1/2-in. wide. The adjustable trolley slides along with the worker to provide maximum mobility
▶ 496/	Miller Grip™ portable/reusable anchorage supports 5,000 lb. ultimate strength; for single user connection; 400 lbs. maximum capacity; color-coded green. Hole diameter – 3/4-in.
▶ 8816-14/	Lightweight, adjustable ShadowLite™ Beam Anchor – high-strength aluminum and bronze; 4.2 lbs.

▶ Rapid Response Program – Same Day Shipping! Consult Customer Care for up-to-date availability.



RA30-1



9065



17D-1



8816-14



496/

Call Customer Care at 800 430-5490.

Call Honeywell Technical Service at 800-873-5242 or visit www.millerfallprotection.com.