

Miller Manyard® Shock-Absorbing Lanyards

- Specially-woven shock-absorbing inner core smoothly expands to reduce fall arrest forces
- After a fall occurs, a warning flag is released

SKU	Material	Number of Legs	Harness Connection	Anchorage Connection	Standard Length
ANSI Z359					
216TWLS-Z7/6FTGN	Green web	One	Locking snap hook	Locking snap hook	6-ft. (1.8 m)
219TWRS-Z7/6FTGN	Green web	One	Locking snap hook	Locking rebar hook	6-ft. (1.8 m)
231TWRS-Z7/6FTGN	Green web	Two	Locking snap hook	Locking rebar hooks	6-ft. (1.8 m)
232TWLS-Z7/6FTGN	Green web	Two	Locking snap hook	Locking snap hooks	6-ft. (1.8 m)
233TWLS-Z7/6FTGN	Green web	One	Web choke-off loop	Locking snap hook	6-ft. (1.8 m)
ANSI A10.32					
216WLS/6FTYL	Yellow web	One	Locking snap hook	Locking snap hook	6-ft. (1.8 m)
219WRS/6FTYL	Yellow web	One	Locking snap hook	Locking rebar hook	6-ft. (1.8 m)
231WRS/6FTYL	Yellow web	Two	Locking snap hook	Locking rebar hooks	6-ft. (1.8 m)
232WLS/6FTYL	Yellow web	Two	Locking snap hook	Locking snap hooks	6-ft. (1.8 m)
233WLS/6FTYL	Yellow web	One	Web choke-off loop	Locking snap hook	6-ft. (1.8 m)
233WRS/6FTYL	Yellow web	One	Web choke-off loop	Locking rebar hook	6-ft. (1.8 m)

Note: Locking snap hook – 3/4-in. (19 mm) gate opening. Locking rebar hook – 2-1/2-in. (63 mm) gate opening.
Meets all applicable OSHA, ANSI and CSA Standards.



Miller Manyard® II Stretchable Shock-Absorbing Lanyards

- Contracts 6-ft. (1.8 m) to 4-ft. (1.2 m) to reduce tripping, snagging, or dragging
- Specially-woven shock-absorbing inner core smoothly expands to reduce fall arrest forces
- After a fall occurs, a warning flag is released

SKU	Material	Number of Legs	Harness Connection	Anchorage Connection	Standard Length
ANSI Z359					
216M-Z7/6FTGN	Webbing	One	Locking snap hook	Locking snap hook	6-ft. (1.8 m)
219M-Z7/6FTGN	Webbing	One	Locking snap hook	Locking rebar hook	6-ft. (1.8 m)
231M-Z7/6FTGN	Webbing	Two	Locking snap hook	Two locking rebar hooks	6-ft. (1.8 m)
232M-Z7/6FTGN	Webbing	Two	Locking snap hook	Two locking snap hooks	6-ft. (1.8 m)
233MORS-Z7/6FTGN	Webbing	One	Web choke-off loop & "O" ring extension	Locking rebar hook	6-ft. (1.8 m)
ANSI A10.32					
216M/6FTGN	Webbing	One	Locking snap hook	Locking snap hook	6-ft. (1.8 m)
219M/6FTGN	Webbing	One	Locking snap hook	Locking rebar hook	6-ft. (1.8 m)
231M/6FTGN	Webbing	Two	Locking snap hook	Two locking rebar hooks	6-ft. (1.8 m)
232M/6FTGN	Webbing	Two	Locking snap hook	Two locking snap hooks	6-ft. (1.8 m)
233MRS/6FTGN	Webbing	One	Web choke-off loop	Locking rebar hook	6-ft. (1.8 m)

Note: Locking snap hook – 3/4-in. (19 mm) gate opening. Locking rebar hook – 2-1/2-in. (63 mm) gate opening.
Meets all applicable OSHA, ANSI and CSA Standards.

