

Miller Welding Harnesses

DESIGNED FOR THE CHALLENGES OF HARSH WELDING ENVIRONMENTS

Lightweight/Comfort Welding Harness

650K/UBL

- Lightweight, comfort welding harness features blue, flame-retardant Nomex webbing to protect against weld splatter
- Inner Kevlar core adds strength and high-temperature resistance

Prevent Suspension Trauma!
(See pg. 18 for details)



Heavy-Duty Welding Harness

850KQC/UBK

- Rugged black Kevlar® webbing for harsh welding environments
- Meets ASTM F887 Arc Test requirements and are rated for arc exposure
- Quick-connect buckles on the chest strap for easy/fast donning



SKU	Size	Back D-Ring	Front D-Ring	Side D-Rings	Chest Strap Buckle	Shoulder Strap Buckles	Leg Strap Buckles	Sub-Pelvic Strap	Special Features
MILLER LIGHTWEIGHT/COMFORT WELDING HARNESSSES									
650K/UBL	U	Yes	Option	No	Mating	Friction	Mating	Yes	Belt loops; pull-up adjustment
650K-7/UBL	U	Yes	Option	Yes	Mating	Friction	Mating	Yes	Belt loops; pull-up adjustment
751K/UBL	U	Yes	Option	No	Mating	—	Mating	Yes	—
850K/UBL	U	Yes	Option	No	Mating	Friction	Mating	Yes	Pull-down adjustment
MILLER HEAVY-DUTY WELDING HARNESSSES									
650KQC-4/UBK	U	Yes	Option	No	Quick-Connect	Friction	Tongue	Yes	Belt loops; pull-up adjustment
650KQC-58/UBK	U	Yes	Option	Yes	Quick-Connect	Friction	Tongue	Yes	Belt loops; pull-up adjustment
850KQC/UBK	U	Yes	Option	No	Quick-Connect	Friction	Quick-Connect	Yes	Pull-down adjustment
850KQC-4/UBK	U	Yes	Option	No	Quick-Connect	Friction	Tongue	Yes	Pull-down adjustment
850KQC-58/UBK	U	Yes	Option	Yes	Quick-Connect	Friction	Tongue	Yes	Pull-down adjustment

SKU numbers listed are for **Universal (Lg./XL)** size. Harnesses are also available in **small/medium, XXL** and **XXXL**, by replacing the "U" in the SKU number with "S/M", "XXL" or "XXXL" (Ex: 650K/XXLBL). For front D-ring vest-style option, add "FD" to the corresponding harness SKU number (Ex: 650KFD/UBL).

Additional Miller Welding Products

Miller Welding Lanyards

SKU	Material	Number of Legs	Harness Connection	Anchorage Connection	Special Features	Standard Length
MILLER WELDING LANYARDS						
ANSI A10.32						
907K/6FTBL	1/4-in. (6 mm) wire rope	One	Locking snap hook	Locking snap hook	SofStop shock absorber w/Nomex cover & Kevlar core	6-ft. (1.8 m)
913K/6FTBL	Nomex/Kevlar webbing	One	Locking snap hook	Locking snap hook	SofStop shock absorber w/Nomex cover & Kevlar core	6-ft. (1.8 m)
940K/6FTBL	Nomex/Kevlar webbing	One	Locking snap hook	Locking snap hook	Double SofStop Pack shock absorber for 12-ft. (3.7 m) free fall with SofStop shock absorber w/Nomex cover & Kevlar core (use w/Miller Shadow Beam Anchor)	6-ft. (1.8 m)
947K/6FTBL	1/4-in. (6 mm) wire rope	One	Locking snap hook	Locking snap hook	Double SofStop Pack shock absorber for 12-ft. (3.7 m) free fall with SofStop shock absorber w/Nomex cover & Kevlar core (use w/Miller Shadow Beam Anchor)	6-ft. (1.8 m)

