

CARPET MAINTENANCE PROCEDURES

CARPET PRE-TREATMENT

- Remove furniture from area to be cleaned
- Dry vacuum carpet before shampoo or extraction cleaning
- Remove gum spots with **CHEWING GUM REMOVER (4524 aerosol)** and pre-treat stains with **SPOT ATTACK (6458 liquid, 4521 aerosol)**
- For heavily soiled traffic lanes, pre-treat with **FIBRE ZONE (6475)** to loosen and emulsify grease and dirt before steam cleaning or shampooing

BONNET CLEANING

- Mix cleaning solution in a sprayer using proper dilution ratio as described on the label
- Dampen bonnet pad with water, do not soak
- Spray bonnet with cleaning solution and place bonnet under machine on carpet, sprayed side down
- Spray carpet approximately 100 square feet at a time, holding sprayer 12-16 inches above carpet, avoid soaking carpet
- Buff carpet over sprayed area in smooth, even strokes from side-to-side in a uniform pattern
- Turn pad over or change when heavily soiled (after 500-1000 square feet), repeat process until carpet is clean
- Allow carpet to dry for 30 minutes to an hour, then vacuum

EXTRACTION

- Dilute (1:128) **VAPOR RUG (6474)** or **FIBRE ZONE (6475)** with warm water in the solution tank according to label directions
- To help assist in foam control add **ANTI-FOAM (6315)** to the recovery tank
- Spray solution from front to rear and agitate solution into the carpet
- Avoid over wetting the carpet
- Make certain to overlap about two inches as you do each section
- After carpet has been completely scrubbed, vacuum using only the vacuum pump, this will pull additional dirt and liquid out of the carpet

DRY FOAM SHAMPOOING

- Dilute (up to 1:25) **FOAM MASTER (6476)** and shampoo in one pass of the machine, first in one direction and then back, overlapping 2 inches
- Allow carpet to dry, then vacuum thoroughly

DEODORIZING

- **CELEBRITY (7169)** carpet deodorizer is a highly concentrated powder formulation designed to overcome strong odors caused by smoking, pets, and more, just sprinkle on and vacuum off to keep carpets clean and fresh

Resilient Floor Care

Finishes

Ultimate 6550

25% Solids

Color: White

Fragnance: Acrylic

Dilution: RTU

pH: 8.5

Floor finish formulation based on the latest generation of modified acrylic polymers that provides the ultimate in initial gloss, gloss retention, and durability. It may be used in low maintenance mop/recoat programs as well as with high-speed burnishing equipment.

Available Package Sizes

4/1 gallon case.....	655041SA
5 gallon pail.....	655005SA
55 gallon drum.....	655055PA

Peak 6561

20% Solids

Color: White

Fragnance: Acrylic

Dilution: RTU

pH: 8.5

Formulation based on the latest generation of modified acrylic polymers that provides unsurpassed leveling, excellent initial gloss, gloss retention, and durability. It may be used in low maintenance mop/recoat programs as well as with high-speed burnishing equipment.

Available Package Sizes

4/1 gallon case.....	656141SA
5 gallon pail.....	656105SA
55 gallon drum.....	656155PA

