APPROX WEIGHT: 448.72 lbs. TELESCOPING LIFT MASTER ONE - LM-1T-4-30 DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!!! *** ANY ADDITIONS. DELETIONS. OR OMISSIONS MUST ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF *3D VIEW SHOWN CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY BE CORRECTED ON THIS DRAWING AS THIS DRAWING THOSE DIMENSIONS WITH YOUR SALESPERSON FOR RFFFRFNCF* WILL BE CONSIDERED ALL INCLUSIVE *** 152 9/16" EXTENDED 84 9/16" RFTRACTED 30" FORK 38" **POCKET CENTERS USABLE FORK POCKET:** 2 1/2" x 7 1/2" CENTERS OF **GRAVITY** STANDARD FEATURES 12 15/16" MODEL NUMBER: LM-1T-4-30 CAPACITY: 4.000 LBS LOST LOAD - 460 LBS 3" **OVERALL WIDTH - 38"** LENGTH (EXTENDED) - 152 9/16" LENGTH (RETRACTED) - 84 9/16" 13 1**/**16" **VERTICAL** OVERALL HEIGHT - 22 1/2" 22 1/2" CTR. OF USABLE FORK POCKET - 2 1/2" x 7 1/2" **GRAVITY** 30" FORK POCKET CENTERS 36" MINIMUM HOOK POINT 31 3/4" 144" MAXIMUM HOOK POINT RETRACTED EFFECTIVE THICKNESS: LESS THAN 1" **CENTER OF GRAVITY** 48" EXTENDED I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS SPECIAL FEATURES CENTER OF GRAVITY REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO NONE Ρ CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE Ρ NEVER EXCEED LOAD CENTER RATING PER AND LOCAL REGULATIONS AND STANDARDS. R ALL SPECIAL UNITS ARE NON-RETURNABLE FORK TRUCK MANUFACTURER'S GUIDLINES. 0 [] As drawn 1 As marked DO NOT USE THIS FORK TRUCK ATTACHMENT V IF LOAD WILL EXCEED FORK TRUCK Α Signed: Date: MANUFACTURER'S LOAD CENTER RATING. LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING DISTRIBUTOR'S NAME: P.O.# W.O.# X VESTIL MANUFACTURING DRAWN BY: ND DATE: 7/31/09 SALES: X 36" DISTANCE 48" 60" 72" 84" 96" 108" 120" 132" 144" REFERENCE: X SCALE: 1:24 FILE NAME: 4000 3750 3500 3250 2250 2000 1750 3000 2750 2500 CAPACITY QUOTED LEAD TIME: X QUOTE # 08-007-202 Χ