



Absorbent SOC

Specialty absorbent SOC can be used around a facility when a pad or roll may not be sufficient. They are dependable, flexible tubes that contain and absorb liquids. SOC mold around corners and conform to uneven surfaces to soak up spills and drips, preventing fluid from escaping to other areas.



ALLWIK® Universal SOC

- All-purpose polypropylene SOC
- Suitable for most industrial applications
- Wringable and can be incinerated

Catalog #	Type	Size	Qty.
AW124	SOC	3"x12'	4
AW806	SOC	3"x8'	6
AW430	SOC	3"x4'	30
AW412	SOC	3"x4'	12



BASIC Universal SOC

- NEW economical absorbent SOC with a cellulose fill
- Suitable for most non-aggressive fluids

Catalog #	Type	Size	Qty.
BSC40	SOC	3"x42"	40
BSC20	SOC	3"x42"	20



SLIKWIK® Universal SOC

- Corn cob-filled SOC
- Exceptional value for picking up of all non-aggressive liquids

Catalog #	Type	Size	Qty.
SW46	SOC	3"x42"	40



Re-Form™ Universal SOC

- Made from recycled newsprint and other cellulose
- Absorbs oils, coolants, solvents and water-based fluid

Catalog #	Type	Size	Qty.
MS-124	SOC	3"x12'	4
MS-806	SOC	3"x8'	6
MS-50	SOC	3"x4'	40
MS-412	SOC	3"x4'	12



Re-Form™ Oil Only SOC

- Made from 80% all natural cotton fibers
- Absorbs oil, grease, transmission fluid, coolant and other liquids.
- Repels water and floats for outdoor applications

Catalog #	Type	Size	Qty.
RFO412	SOC	3"x4'	12



Cobra Coil® Universal SOC

- Vermiculite-filled SOC
- Excellent for diking applications
- Suitable for all liquids including aggressive chemicals

Catalog #	Type	Size	Qty.
CC440V	SOC	3"x4'	40
CC400V	SOC	3"x4'	12



HAZWIK® SOC

- Absorbs chemicals, acids and bases
- Flexible design is easily molded around spills

Catalog #	Type	Size	Qty.
HAZ124	SOC	3"x12'	4
HAZ412	SOC	3"x4'	12



Oil Only SOC

- Specialized oil only polypropylene SOC
- Absorbs oil and petroleum based liquids while repelling water
- Wringable and can be incinerated

Catalog #	Type	Size	Qty.
OIL124	SOC	3"x12'	4
OIL806	SOC	3"x8'	6
OIL430	SOC	3"x4'	30
OIL412	SOC	3"x4'	12



SOC Usage Tips:

Use these tips to help ensure that you get the most out of your SOC:

- Clean-up all loose materials, rags and other debris around the spill
- SOC work best when they lay flat against the floor
- Replace your SOC when liquid begins pooling or seeping underneath
- When installing your SOC, shake vigorously to evenly distribute absorbent within the SOC
- Overlap the ends of your SOC approximately 5" to extend your spill protection

View full product specs on page 378.