



FACE PROTECTION ICONS TO LOOK FOR

Throughout the Face Protection section of this catalog, you will find a number of icons. Each icon packs a lot of information into a little bit of space. Don't take them lightly. When choosing personal protection, consider whether the "mark" is appropriate for your application.



When you see the ANSI Z87.1+ Certified icon, you know that both Gateway Safety and an independent, third-party laboratory regularly test and certify that this product meets or exceeds the ANSI Z87.1+ standard.



When you see the CSA Z94.3 Certified icon, you know that both Gateway Safety and an independent, third-party laboratory regularly test and certify that this product meets or exceeds the CSA Z94.3 standard.



When you see the Meets ANSI Z87.1+ icon, you know that Gateway Safety regularly tests and self-certifies that this product meets or exceeds the ANSI Z87.1+ standard.



When you see the Meets CSA Z94.3 icon, you know that Gateway Safety regularly tests and certifies that this product meets or exceeds the CSA Z94.3 standard. However, sales do not warrant independent verification.



When you see the c-UL-us LISTED icon, you know that Underwriters Laboratories is the independent, third-party agency that has certified that this product meets the ANSI Z87+ and CSA Z94.3 standards. Confirmation can be found in their 'Online Certifications Directory' at www.ul.com.



When you see the 99.9% UV-A & UV-B Protection icon, you know that Gateway Safety regularly tests and certifies that this product blocks 99.9% of UV-A and UV-B radiation.

All certification information is accurate as of the print date of this catalog. For updated information, visit Underwriters Laboratories 'Online Certifications Directory' at www.ul.com or contact Gateway Safety's customer service department at 800-822-5347.

All Gateway Safety products come with a limited warranty. See back cover for warranty information.

VISOR SELECTION CHART

More than ornamental, each visor option serves a specific function. This visor selection chart provides a general usage guideline. However, always consult your safety director to determine the proper visor option for each application. All Gateway Safety visors block 99.9% of UV-A and UV-B light, up to 380 nm.



impact protection. 91% VLT.

GRAY VISORS

Primarily used for outdoor applications. Minimizes glare that can result in eye strain and fatigue. 18% VLT.

ANTI-FOG VISORS

Even in the most extreme environments, Gateway Safety's Anti-Fog coating helps minimize, or even eliminate, visor fogging.

GOLD MIRROR VISORS

Made with real gold that helps reflect heat.

IR FILTER VISORS

For use around light welding or light brazing/ cutting.

VLT (Visual Light Transmittance) is the amount of visible light that gets through the lens.