



# Ultra 25 Floor Finish



## Floor Care

### DESCRIPTION

The ultimate in appearance and durability this product gives you maximum protection in fewer coats. Save time and labor dollars while enhancing the beauty of your floors. Maintenance has never been so easy. Perfect for the high speed and propane burnishers, this product also maintains its high appearance level even when buffing is not possible. Perfectly clear and non-yellowing, each film coat molecularly bonds together to provide extended durability. This product is easy to apply with mop or applicator. This product is acceptable for use in nonprocessing areas of food processing establishments (formerly USDA Category C1).

### DIRECTIONS

Read the entire container label before using the product.

1. Strip floor entirely of old finish using one of our recommended floor strippers.
2. Apply finish using a clean finish mop or applicator. 3 to 7 coats may be applied per application. Allow 30-45 minutes for finish to dry completely before recoating.
3. Allow at least 2 hours after final coat dries before burnishing (Note: It is always recommended to wait 24 hours before burnishing, however this product can be burnished 2 hours after product dries).
4. Maintain floor by dust mopping and spot mopping as needed.
5. Auto scrub with our recommended floor cleaner using a red pad before burnishing.
6. Periodically deep scrub with our recommended floor cleaner and a blue pad before recoating.

**For use on hard surfaces such as concrete, terrazzo, marble, or granite:** It is recommended that two coats of sealer be applied to surface to seal floor properly. Follow with 3-5 coats of finish. Burnish and maintain as normal.

### FIRST AID

Have the product container or label with you when calling a physician or when going for treatment.

**IF IN EYES:** Immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses after 5 minutes, if worn. Get medical attention if irritation develops and persists.

**IF ON SKIN:** Immediately flush skin with soap and water. Call a physician if irritation develops and persists. Remove contaminated clothing and wash before reuse.

**IF SWALLOWED:** Call a physician immediately. Do NOT induce vomiting unless directed to do so by qualified medical personnel. Never give anything by mouth to an unconscious person.

• For additional information, see Material Safety Data Sheet (MSDS) for this material.

### APPLICATIONS

Premium high (daily) maintenance finish for use in:

- Food processing establishments
- Office buildings
- Hospitals and nursing homes
- Airports and retail establishments
- Schools

### BENEFITS

- High solids – requires fewer coats/less labor
- Durable
- High off-the-mop gloss
- Easy to maintain
- Will not yellow

### SPECIFICATIONS

Color.....White  
Fragrance.....Characteristic  
pH Range.....8.0-8.5  
Dilution.....RTU  
Density.....8.65  
% Non-Volatile Solids.....25%  
Coverage.....2000 sq. ft./gal.

### PACKAGING

ITEM #	SIZE
50324 .....	4/1 gal.
50325 .....	5 gal.

Distributed by:

**HANTOVER**

10301 Hickman Mills Dr., Suite 200  
Kansas City, MO 64137  
800.821.2227 • FAX 816.761.0044  
www.hantover.com