

## CONNECTING DEVICES

**BackBiter® lanyard and T-BAK™ PFL offers the ultimate in tie-back safety**

The webbing and snap hooks of regular lanyards are not designed to withstand the rigors of tying back. The innovative BackBiter® Tie-Back Lanyard and T-BAK™ Tie-Back PFL were designed from top to bottom for tie-back use. Meets all applicable OSHA, ANSI Z359, ANSI A10.32 and CSA standards.



### Miller BackBiter® Tie-Back Lanyards

- All-in-one 6 ft. lanyard with SofStop® shock absorber and cross-arm anchorage connector
- Unique Miller 5K® snap hook with 5,000 lbs. gate load capacity from any angle for greater safety
- Heavy-duty webbing with 5-times more abrasion resistance
- SofStop® shock absorber pack is designed with a special woven inner core that smoothly expands to reduce fall arrest forces
- Heavy duty tubular web outer jacket serves as a back-up lanyard for added safety

SKU	Number of Legs	Anchorage Connection	Harness Connection
▶ 913B/6FTGN	One	Locking 5K snap hook	Locking snap hook
▶ 8798B/6FTGN	Two	Locking 5K snap hook	Locking snap hooks

▶ Rapid Response Program – *Same Day Shipping!* Consult Customer Care for up-to-date availability.



### Miller Turbo T-BAK™ Personal Fall Limiter

- The first and only retractable designed to tie-back anywhere along the lifeline.
- Cost-effective alternative to tie-back, shock-absorbing lanyards
- All-in-one design – 7.5 ft. working capacity and anchorage connector
- Designed for anchoring below a user's harness back D-ring for greater safety
- Integrated shock absorber with load indicator
- Only tie-back retractable that meets ANSI Z359
- The Miller Turbo T-BAK Fall Protection System easily adapts two units for 100% tie-off fall protection

SKU	Description and Unit Connector
MFLT-1/7.5FT	Turbo T-BAK without unit connector
▶ MFLT-2/7.5FT	Turbo T-BAK with a 17D-1 steel twist-lock carabiner
▶ *MFLT-3/7.5FT	Turbo T-BAK with a 17D-2 lightweight, aluminum twist-lock carabiner
MFLT-4/7.5FT	Turbo T-BAK with a locking snap hook with 3/4-in. gate opening
▶ MFLT-5/7.5FT	Turbo T-BAK with an ANSI Z359-compliant snap hook with 3/4-in. gate opening

### Miller Turbo T-BAK™ Fall Protection System

- ▶ MFLTB-1/7.5FT Twin Turbo D-ring Connector with two (2) MFLT-1/7.5FT Turbo T-BAK units

▶ Rapid Response Program – *Same Day Shipping!* Consult Customer Care for up-to-date availability.

\*Does not meet ANSI Z359



by Honeywell

Call Customer Care at 800 430-5490.  
Call Honeywell Technical Service at 800-873-5242 or visit [www.millerfallprotection.com](http://www.millerfallprotection.com).



## Honeywell Safety Products

PERSONAL PROTECTIVE EQUIPMENT 2013 – U.S.