



**TY 127 S**

**Frock**

**TY 210 S WH xx 0030 00**  
**TY 210 S WH xx 0030 PI**  
 Serged seams  
 Collar  
 Front snap closure  
 SM-7X



**Frock**

**TY 211 S WH xx 0030 00**  
 Serged seams  
 Collar  
 Front snap closure  
 Elastic wrists  
 Knee length  
 SM-7X



**Frock**

**TY 216 S WH xx 0030 00**  
 Serged seams  
 Mandarin collar  
 Front snap closure  
 Elastic wrists  
 SM-5X



**Labcoat**

**TY 212 S WH xx 0030 00**  
**TY 212 S WH xx 0030 PI**  
**TY 212 S WH xx 0030 NF**  
 Serged seams  
 Collar  
 Front snap closure  
 Two pockets  
 SM-7X



**Shirt**

**TY 303 S WH xx 0050 00** SM-7X  
**TY 303 S WH xx 0050 PI** SM-3X  
 Serged seams  
 Collar  
 Front snap closure  
 Long sleeve  
 SM-7X



**Pants**

**TY 350 S WH xx 0050 00** SM-7X  
**TY 350 S WH xx 0050 PI** SM-3X  
 Serged seams  
 Elastic waist



**Apron**

**TY 273 B WH xx 0100 00**  
**TY 273 B WH xx 0100 PI**  
 Bound seams  
 Bound neck & ties  
 Bib style  
 28" x 36"  
 One size fits all



**Sleeve**

**TY 500 S WH xx 0200 00**  
**TY 500 S WH xx 0200 NF**  
 Serged seams  
 Elastic top  
 Elastic wrist  
 18" length  
 One size fits all



**Hood**

**TY 657 S WH xx 0100 00**  
 Serged seams  
 Pullover  
 Elastic face  
 Shoulder length  
 One size fits all



Only TV option codes are TAA compliant.

<sup>1</sup>Respirator fit hoods are designed with a longer zipper, extending to the chin for complete coverage of the neck area. Standard hoods only extend to the neck. See page 5 for photos. Bound and sewn seams and closures have less barrier than fabric.

Serged and/or bound seams are degraded by some hazardous liquid chemicals, such as strong acids, and should not be worn when these chemicals are present.

Tyvek® with Friction Coating (FC) has been specially treated to promote ink/coating adhesion. This treatment lowers the typical bulk liquid holdout values for Tyvek® fabric. Products with this treatment offer limited bulk liquid holdout. If barrier protection from liquid splash is required, please consider a non-treated Tyvek® style or other substrate.

Note: Not all sizes available in all styles.

**WARNING:** Tyvek® should not be used around heat, flames, sparks or in potentially flammable or explosive environments. Garments made of Tyvek® fabrics should have slip-resistant or anti-slip materials on the outer surface of boots, shoe covers, or other garment surfaces in conditions where slipping could occur.

Certain accessory items are also identified as Make to Order. Stock/Make to Order designations are based on sales volume and production efficiencies. Therefore, designations are subject to change without notice.