


No. 703D

- Hard wrought steel and hardened steel bodies for strength
- Hardened steel staples resist cutting and sawing
- Hardened steel locking eyes for strong cut resistance
- Tamper proof hinges help resist prying




General Use Hasps

Product Number	Description	List Price (Each)	Shelf Pack Quantity	Master Carton Quantity	Hasp Length	Accepts Shackle Dia. Up To:	Hasp Length (Metric)	Accepts Shackle Dia. (Metric) Up To:
702D	2-1/2" (64mm) Hard Wrought Steel Body	3.63	4	24	2-1/2"	9/32"	6.4cm	7mm
703D	3-1/2" (89mm) Hard Wrought Steel Body	4.30	4	24	3-1/2"	11/32"	9cm	9mm
704DPF	4-1/2" (11cm) Hard Wrought Steel Body	5.35	4	24	4-1/2"	1/2"	11cm	13mm
706D	6" (15cm) Hardened Steel Body with Reinforced Plate	10.14	4	24	6"	9/16"	15cm	14mm



- Hasps with integral locking mechanisms for security and convenience
- Hardened steel hasps with laminated steel lock body
- Ribbed hasp plate for extra strength
- Hardened steel locking eye for strong cut resistance



No. 450 Padlock

Product Number	Description	List Price (Each)	Shelf Pack Quantity	Master Carton Quantity	Hasp Length	Accepts Shackle Dia. Up To:	Hasp Length (Metric)	Accepts Shackle Dia. (Metric) Up To:
General-Use Hasplocks, Warded Mechanism								
450D	Keyed Different	13.67	4	24	4-1/2"	1-3/4"	11cm	44mm

LOCK LUBRICANT



- Designed specifically for padlocks, door locks, automotive, marine, and multipurpose applications
- Keep your locks operating like new in any environment Snow, rain, freezing temperatures, marine, extreme heat
- Designed specifically for precision lock components prevents rust, corrosion, and loosens stuck parts
- Precision Nozzle Designed specifically for precise application inside locking devices
- Synthetic oil with PTFE formula Provides a long lasting protective shield against dust, dirt, salt and moisture
- Outstanding temperature range Synthetic formula operates in cold weather (-45°F) when mineral based aerosols will not. Prevents water build up & freezing lock components
- Non-toxic & biodegradable Better for the environment
- Prolong the life of your lock Apply 2-3 drops in key hole and shackle openings every three to six months for trouble free operation

No. 2300D

Lock Lubricant

Product Number	Description	List Price (Each)	Master Carton Quantity
2300D	Lock Lubricant	5.26	12